# Anderson Street Subdivision

## Stages 3

# Winchelsea

NOTES:

GENERAL:

1. ALL WORKS ARE TO BE CARRIED OUT IN ACCORDANCE WITH THE WATER SERVICES ASSOCIATION OF AUSTRALIA WATER CODE 03-2011 AND SEWER CODE 02-2002 MRWA VERSION AND RELEVANT BARWON WATER SUPPLEMENTARY DOCUMENTATION.

2. CONTACT PRIOR TO COMMENCEMENT OF WORKS:

   SURFCOAST SHIRE
   POWERCOR
   WESTAR
   TELECOMMUNICATIONS PROVIDERS
   VICTORIAN WORKCOVER AUTHORITY

3. BARWON WATER IS TO BE NOTIFIED 7 CLEAR DAYS PRIOR TO THE COMMENCEMENT OF WORKS.

4. PROPERTY OWNERS ARE TO BE NOTIFIED BY THE CONSULTANT IN WRITING 14 CLEAR DAYS PRIOR TO THE COMMENCEMENT OF WORKS.

5. COPY OF CADASTRAL MAP GRID (MGA) CONNECTION AND COPY OF AUSTRALIAN HEIGHT DATUM (AHD) CONNECTION IS TO BE PROVIDED BY THE CONTRACTOR.

6. THE WORKS SHALL BE EFFECTED BETWEEN THE HOURS OF 8.00AM AND 5.00PM MONDAY-FRIDAY. IN THE EVENT THAT WORKS ARE TO BE EFFECTED OUTSIDE THESE WORKING HOURS A LETTER REQUESTING APPROVAL FOR SUCH OUT OF HOURS WORK SHALL BE LODGED WITH THE SENIOR QUALITY AUDITOR.

7. ALL SERVICES ARE TO BE LOCATED ON SITE PRIOR TO ANY EXCAVATION.

8. IL's OF EXISTING SEWER AND WATER MAINS ARE TO BE CHECKED PRIOR TO COMMENCEMENT OF WORKS.

9. CLASS 2 BACKFILL TO BE USED UNDER DRIVEWAYS FOR WATER AND SEWER.

10. PVC JOINTS TO HAVE ELASTOMERIC SEALS.

11. THE CONTRACTOR SHALL COMPLY WITH SAFETY REQUIREMENTS RELATING TO WORKING NEAR POWER LINES AS SET OUT BY THE CHIEF ELECTRICAL INSPECTOR. WHERE NECESSARY, AN ACCREDITED TRAINED SPOTTER IS TO BE PROVIDED.

12. ANY WORK INVOLVING THE REMOVAL (CUTTING AND HANDLING), STORAGE, TRANSPORTATION AND DISPOSAL OF WASTE ASBESTOS CEMENT (AC) PIPES MUST BE CARRIED OUT IN ACCORDANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY (ASBESTOS) REGULATIONS 1992 AND RELEVANT CODES OF PRACTICE (REMOVAL), THE ENVIRONMENTAL PROTECTION (PRESCRIBED WASTE) REGULATIONS 1998 (STORAGE, TRANSPORTATION AND DISPOSAL), AND BARWON WATER'S SAFETY MANAGEMENT SYSTEM 'SAFEAS'. A CERTIFICATE OF DISPOSAL IS TO BE INCLUDED WITH 'AS CONSTRUCTED' PACKAGE SUBMITTED TO BARWON WATER UPON PROJECT COMPLETION.

WATER:

13. ALL ALLOTMENTS ARE TO BE PROVIDED WITH A WATER SERVICE AS PART OF WATER RETICULATION WORKS.

    THE WATER MAIN IS TO BE TAPPED USING A TAPPING SADDLE AND PRESSURE FERRULE (FERRULE IS TO BE LEFT OPEN). A MINIMUM SIZE SERVICE (ie 20mm COPPER, 25mm PE) IS THEN TO BE EXTENDED TO A POINT 500mm WITHIN THE PROPERTY. THE SERVICE IS TO BE A CONTINUOUS LENGTH WITH NO JOINTS. IN THE CASE OF PE OR ANY OTHER NON-METALLIC SERVICE BEING INSTALLED, A COPPER TRACE WIRE IS TO BE INCORPORATED. A BURIED BALL VALVE IS TO BE PLACED AT THE END OF THE SERVICE AND BACKFILLED WITH SAND TO DESIGN SURFACE LEVEL. A PLASTIC PROTECTIVE COVER IS TO BE PLACED OVER THE BALL VALVE. THE BALL VALVE (FEMALE END) IS TO BE PLUGGED WITH A PLASTIC CAP. DETECTOR TAPE FROM THE BALL VALVE TO BE RUN TO SURFACE LEVEL.

14. PE PIPE TO BE LAID IN ACCORDANCE WITH WSA-01. LONG RADIUS BENDS OR DEFLECTION ONLY TO BE USED FOR CHANGE OF DIRECTION. NO COMPRESSION BENDS TO BE USED.

15. THRUST RESTRAINTS HAVE BEEN DESIGNED FOR 50 KPa ALLOWABLE BEARING PRESSURE OF GROUND (STIFF CLAY) AND ARE TO BE CONSTRUCTED AS PER WSAA 2011 STANDARD DRAWING WAT-1206. WHERE CONCRETE THRUST BLOCKS ARE NOMINATED THEY ARE TO BE CONSTRUCTED IN ACCORDANCE WITH WAT-1205. THE CONTRACTOR SHALL CONFIRM THE ACTUAL GROUND CONDITIONS WITH THE SUPERINTENDENT PRIOR TO CONSTRUCTING RESTRAINTS.

16. MARKER POSTS ARE TO BE PLACED AT STOP VALVES AND FIRE PLUGS IN ACCORDANCE WITH WSAA AND CFA GUIDELINES.

17. MONT TAP (MT) AND ANY TAPPING WITHIN THE ROAD PAVEMENT TO HAVE HEAVY DUTY COVER (FITZROY BOX 150mm x 125mm).

18. ALL POTABLE WATER SUPPLY MAINS MUST BE CLEANED, SWABBED, PRESSURE TESTED, DISINFECTED (WHERE REQUIRED) AND WATER QUALITY TESTED STRICTLY IN ACCORDANCE WITH WSAA 03-2011 MRWA EDITION AND WATER AGENCY SPECIFICATIONS IN THE FOLLOWING SEQUENCE.

    — FOLLOWING CONNECTION OF THE NEW WATER MAINS TO THE EXISTING SUPPLY SYSTEM, LINES ARE TO BE SWABBED IN ACCORDANCE WITH SECTIONS 6.7 AND 18 OF WSAA 03-2011 MRWA EDITION.

      SWAB ENTRY AND DISCHARGE POINTS CAN BE THROUGH FIREPLUGS FOR DN100-DN200mm WATER MAINS OR INSERTED DIRECTLY INTO THE MAIN DURING PIPE LAYING. THE LOCATION AND DIRECTION OF SWABS ARE SHOWN ON THE PLAN.

      SWAB DISCHARGE CONTROL UNITS WILL BE REQUIRED FOR ALL LARGER PIPE SIZES OR ANY PIPE SIZE WHERE A SWAB CANNOT BE DISCHARGED THROUGH A FIREPLUG (REFER WAT-1321-M).

    — FOLLOWING SWABBING ALL MAINS ARE TO BE HYDROSTATIC PRESSURE TESTED AT THE CORRECT TEST PRESSURE CORRESPONDING TO THE NOMINATED DESIGN HEAD WITH ALL TEST RESULTS RECORDED AND INCLUDED WITH THE 'AS CONSTRUCTED' PACKAGE SUBMITTED TO BARWON WATER UPON PROJECT COMPLETION.

      THE CONTRACTOR MUST GIVE BARWON WATER'S SENIOR QUALITY AUDITOR 3 (THREE) CLEAR WORKING DAYS NOTICE IN WRITING OF THE DATE AND TIME OF THE PROPOSED TEST.

    — FOR WATER MAINS 225mm AND ABOVE OR WHERE DIRECTED BY BARWON WATER'S SENIOR QUALITY AUDITOR (ie. FOR MAINS SMALLER THAN 225mm OR EXISTING MAINS THAT ARE LIKELY TO BE CONTAMINATED FROM CONSTRUCTION WORKS), WATER MAINS ARE TO BE DISINFECTED, FLUSHED AND WATER QUALITY TESTED IN ACCORDANCE WITH SECTIONS 19.5 AND 20 OF WSAA 03-2011 MRWA EDITION AND MRWA SPECIFICATIONS 04-01 AND 04-02.

      THE CONTRACTOR/CONSULTANT TO ARRANGE TESTING WITH BARWON WATER TO UNDERTAKE FLUSHING.

      A NATA REGISTERED LABORATORY IS TO BE ENGAGED TO COLLECT AND TEST WATER SAMPLES TO ENSURE THE MAINS ARE SUITABLE FOR COMMISSIONING WITH ALL TEST RESULTS RECORDED AND INCLUDED WITH THE 'AS CONSTRUCTED' PACKAGE SUBMITTED TO BARWON WATER UPON PROJECT COMPLETION.

SEWER:

19. "WARNING; ENTRY INTO ANY MANHOLE IS CONTROLLED BY CONFINED SPACE REGULATIONS BEING "OCCUPATIONAL HEALTH AND SAFETY (CONFINED SPACES) REGULATIONS 1996, STATUTORY RULE No 148/1996 AND A.S.2865-1995 SAFE WORKING IN CONFINED SPACES". PERSON(s) REQUIRING ACCESS TO A BARWON WATER MANHOLE AS PART OF THE DEVELOPMENT WORKS PROCESS MUST CONTACT THE SENIOR QUALITY AUDITOR Ph 03-5226 9204 FOR ENTRY REQUIREMENTS".

    DURING THE CONSTRUCTION OF WORKS TO GAIN ACCESS TO A BARWON WATER MANHOLE THE PROCEDURE AS OUTLINED IN THE ATTACHED FLOWCHART IS TO BE FOLLOWED, AND THE "CONFINED SPACE ENTRY PERMIT APPLICATION FORM" (ALSO ATTACHED) IS TO BE COMPLETED AND LODGED WITH THE SENIOR QUALITY AUDITOR 3 (THREE) CLEAR WORKING DAYS PRIOR TO ENTRY.

20. WHERE FUTURE SEWER MAINS ARE INDICATED, A 150mm ACCESS COUPLING AND CAP ARE TO BE PLACED OUT OF THE MANHOLE.

21. MANHOLE DROPS ARE TO BE CONSTRUCTED AS PER STANDARD DRAWING SEW-1306-V AND BRACED AT 1.0m C/C ON MANHOLE WALL.

22. ALL SEWERS ARE TO BE PVC SN8 UNLESS NOTED OTHERWISE.

23. ALL END OF LINES ARE TO HAVE A TERMINAL MAINTENANCE SHAFT AS PER BARWON WATER DETAIL DRAWING 70095.

24. CURVED SEWER MAINS AND MAINS CROSSING UNDER ROAD PAVEMENT TO HAVE DETECTOR TAPE.

25. PVC SEWER LENGTHS TO NOT EXCEED 3m FOR CURVED SECTIONS OF SEWER MAIN.

26. ALL EXCAVATIONS AROUND NEWLY CONSTRUCTED MANHOLES TO BE BACKFILLED WITH 3% CEMENT STABILIZED SAND.

27. ALL MANHOLE JOINTS, INCLUDING DROPS ARE TO BE SEALED WITH FERROPRE OR APPROVED EQUIVALENT.

28. DIAMETERS OF MANHOLES:
    - MINIMUM MANHOLE DIAMETER SHALL BE 1050mm.
    - WHERE THERE ARE 2 OR MORE INTERNAL DROPS A 1500mm DIAMETER MANHOLE SHALL BE USED.
    - WHERE A SEWER IS ≥DN300 A 1500mm DIAMETER MANHOLE SHALL BE USED.
    - WHERE THE SEWER IS DEEPER THAN 3.0m, 1500mm DIAMETER MANHOLES ARE TO BE USED.

SPECIAL:

29. WATER RESTRICTIONS ARE TO APPLY FROM MIDNIGHT JUNE 30TH 2006, IN ACCORDANCE WITH BY-LAW No 187. ONLY TRIGGER HOSES (MAXIMUM SIZE 25mm) MAY BE USED FOR CONSTRUCTION WORK NOT INCLUDING TRENCHING UNLESS OTHERWISE EXEMPTED BY THE AUTHORITY IN WRITING. MECHANICAL COMPACTION IS TO BE USED IN ACCORDANCE WITH MRWA SPECIFICATION 04-03 FOR TRENCH WORKS UNTIL FURTHER NOTICE.

30. MECHANICAL COMPACTION IS REQUIRED FOR ALL TRENCH WORKS. TRENCH COMPACTION RESULTS ARE TO BE FORWARDED BY THE CONSULTANT TO BARWON WATER WITH 'AS CONSTRUCTED' PACKAGE.

31. CLEANING, DISINFECTION AND TESTING OF DRINKING WATER AND/OR RECYCLED WATER MAINS IS TO BE IN ACCORDANCE WITH BARWON WATER'S "WATER QUALITY GUIDANCE FOR COMMISSIONING ASSETS IN CONTACT WITH POTABLE WATER OR CLASS A RECYCLED WATER" DOCUMENT (DATED 24 SEPTEMBER 2015).

32. SHUTDOWN WORKS ARE TO TAKE PLACE BETWEEN THE HOURS OF 9:00am AND 1:00pm. A MEETING IS TO BE HELD BETWEEN BARWON WATER, THE CONSULTING ENGINEER AND THE CONTRACTOR AT LEAST 10 DAYS PRIOR TO THE PROPOSED SHUTDOWN WORKS TO DISCUSS AND AGREE OF THE DATE AND TIME OF THE SHUTDOWN AND SHUTDOWN PROCEDURE.

ACCEPTED BY BARWON WATER

WORKS SHALL NOT COMMENCE UNTIL PLANS SIGNED BY BARWON WATER

SIGNED_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

LAND DEVELOPMENT CO-ORDINATOR
DEVELOPMENT SERVICES

## CONSTRUCTION NOTES

1. CONSTRUCTION OF SEWER AND WATER MAINS TO BE IN ACCORDANCE WITH BARWON WATER STANDARD SPECIFICATIONS "CONSTRUCTION OF GRAVITY SEWERS AND RISING MAINS" AND "CONSTRUCTION OF WATER MAINS".
2. EVERY ENDEAVOUR TO ENSURE THE LOCATION OF ALL EXISTING SERVICES ON THE PLAN ARE CORRECT HOWEVER ACTUAL LOCATIONS ARE TO BE CHECKED ON SITE PRIOR TO COMMENCEMENT OF EXCAVATION.
3. NOMINAL SIZE OF WATER MAINS INDICATED IN MILLIMETERS, OFFSETS ARE INDICATED IN METRES.
4. ALL SEWER PIPES ARE 150 Ø mm UNLESS OTHERWISE SHOWN.

### PIPE TYPES

| | |
|---|---|
| ASBESTOS CEMENT | AC |
| CAST IRON CEMENT LINED | CICL |
| DUCTILED CEMENT LINED | DICL |
| MILD STEEL CEMENT LINED | MSCL |
| POLYVINYL CHLORIDE | PVC |
| POLYETHELENE (AS SPECIFIED) | PE |
| REINFORCED CONCRETE | RC |
| VITREOUS CLAY | VC |

### FITTINGS AND SYMBOLS

| WATER | SEWER |
|---|---|
| CHANGE OF PIPE SIZE | TYPE "A" JUMP UP |
| MAINS NOT CONNECTED | TYPE "B" JUMP UP |
| MAINS IN CONDUIT | TYPE "C" SLIDE LINE |
| VALVE | OBLIQUE JUNCTION |
| NON RETURN VALVE | TYPE "A" SPECIAL |
| FIRE PLUG | TYPE "TM" SPECIAL |
| DEAD END CAP | TYPE "B" SPECIAL |

### OTHER U/G SERVICES

EXISTING WATER MAIN
STORM WATER
GAS
TELSTRA
ELECTRICITY ● (POLE)
EXISTING SEWER

PETER BERRY & ASSOCIATES PTY LTD
153 YARRA STREET, GEELONG 3220 TEL 5223 2799 FAX 5223 2901

| AMENDMENTS | | |
|---|---|---|
| REV | DESCRIPTION | DATE |

EXTENSION No L014287

ANDERSON STREET SUBDIVISION - STAGE
WINCHELSEA
SHEET 1 OF 4

| DESIGNED | DRAWN | CHECKED | SCALES - PLAN - SECTIONS - HORIZ : VERT : |
|---|---|---|---|
| JULY '17 D.L. BERRY | JULY '17 D.L. BERRY | D.L. BERRY | A1 |
| MGR. PETER BERRY | EXECUTIVE MGR. | | REVISION : A |

| SURVEY MARKS AND LOCATIONS | LEVELS |
|---|---|
| Ex PSM 24 MIRNEE - (SMES) | 92.354 |
| TBM 'A' STAR PICKET - LOT 53 | 90.99 |
| TBM 'B' NAIL IN DUMPY PEG - LOT 46 | 92.00 |
| TBM 'C' STAR PICKET - LOT 42 | 92.14 |

## TOTAL WORKS

| NEW SEWER MAINS | | |
|---|---|---|
| SIZE | TYPE | LENGTH |
| 150mm | PVC SN8 | 452.15m |

## TOTAL WORKS

| NEW WATER MAINS | | |
|---|---|---|
| SIZE | TYPE | LENGTH |
| 150mm | PVC (CL.12) SERIES 2 ONLY | 144m |
| 100mm | PVC (CL.16) SERIES 1 OR 2 | 24m |
| 100mm | PVC (CL.12) SERIES 2 ONLY | 78m |

## WATER MAIN DETAILS

(REFER - SECTION 19.4 WSAA 03-2002)

| DESIGN PRESSURE (m head) | SYSTEM TEST PRESSURE (m head) |
|---|---|
| 79.2 | 100.0 |

## CONCRETE THRUST RESTRAINT SCHEDULE

(REFER WSAA 2002 STANDARD DRAWING WAT-1205)

| LOCATION OF THRUST BLOCK | NOMINAL PIPE DIAMETER | TYPE OF FITTING | No. OF BLOCKS REQUIRED | AREA(Sm) PER THRUST BLOCK |
|---|---|---|---|---|
| A | 150mm | TEE/CAP | 2 | 0.48 |
| B | 100mm | TEE/CAP | 1 | 0.23 |

NOTE: FOR ALL OTHER BENDS NOT SHOWN IN THIS TABLE, TIMBER THRUST BLOCKS ARE TO BE USED IN ACCORDANCE WITH WAT-1286

## SERVICES LOCATION SCHEDULE

| STREET NAME | TELECOM | GAS | WATER | ELECTRICITY | KERB |
|---|---|---|---|---|---|
| ROWLEY DRIVE | 1.90 E | 2.10 W | 2.70 W | 2.50 E | 4.25 |
| WATERLOO PLAINS CRESCENT | 1.90 N | 2.10 S | 2.70 S | 2.50 N | 4.25 |

## ACCEPTED BY BARWON WATER

WORKS SHALL NOT COMMENCE UNTIL PLANS SIGNED BY BARWON WATER

SIGNED_ - - - - - - - - - - - - - - - - - - -

LAND DEVELOPMENT CO-ORDINATOR
DEVELOPMENT SERVICES

## CONSTRUCTION NOTES

1. CONSTRUCTION OF SEWER AND WATER MAINS TO BE IN ACCORDANCE WITH BARWON WATER STANDARD SPECIFICATIONS "CONSTRUCTION OF GRAVITY SEWERS AND RISING MAINS" AND "CONSTRUCTION OF WATER MAINS".
2. EVERY ENDEAVOUR TO ENSURE THE LOCATION OF ALL EXISTING SERVICES ON THE PLAN ARE CORRECT HOWEVER ACTUAL LOCATIONS ARE TO BE CHECKED ON SITE PRIOR TO COMMENCEMENT OF EXCAVATION.
3. NOMINAL SIZE OF WATER MAINS INDICATED IN MILLIMETERS, OFFSETS ARE INDICATED IN METRES.
4. ALL SEWER PIPES ARE 150 Ø mm UNLESS OTHERWISE SHOWN.

### PIPE TYPES

| | |
|---|---|
| ASBESTOS CEMENT | AC |
| CAST IRON CEMENT LINED | CICL |
| DUCTILED CEMENT LINED | DICL |
| MILD STEEL CEMENT LINED | MSCL |
| POLYVINYL CHLORIDE | PVC |
| POLYETHELENE (AS SPECIFIED) | PE |
| REINFORCED CONCRETE | RC |
| VITREOUS CLAY | VC |

### FITTINGS AND SYMBOLS

| | |
|---|---|
| WATER | SEWER |
| CHANGE OF PIPE SIZE | TYPE "A" JUMP UP |
| MAINS NOT CONNECTED | TYPE "B" JUMP UP |
| MAINS IN CONDUIT | TYPE "C" SLIDE LINE |
| VALVE | OBLIQUE JUNCTION |
| NON RETURN VALVE | TYPE "A" SPECIAL |
| FIRE PLUG | TYPE "TM" SPECIAL |
| DEAD END CAP | TYPE "B" SPECIAL |

### OTHER U/G SERVICES

EXISTING WATER MAIN
STORM WATER
GAS
TELSTRA
ELECTRICITY ● (POLE)
EXISTING SEWER

PETER BERRY & ASSOCIATES PTY LTD
153 YARRA STREET, GEELONG 3220 TEL 5223 2799 FAX 5223 2901

| AMENDMENTS | | |
|---|---|---|
| REV | DESCRIPTION | DATE |

EXTENSION No L014287

ANDERSON STREET SUBDIVISION - STAGE 3
WINCHELSEA
SHEET 2 OF 4

| DESIGNED | DRAWN | CHECKED | SCALES - PLAN - 1:500 SECTIONS - HORIZ : VERT : |
|---|---|---|---|
| JULY '17 D.L. BERRY | JULY '17 D.L. BERRY | D.L. BERRY | |
| MGR. PETER BERRY | EXECUTIVE MGR. | | REVISION : A |

A1




ACCEPTED BY BARWON WATER

WORKS SHALL NOT COMMENCE UNTIL PLANS SIGNED BY BARWON WATER

NOTE:

150mm DIAMETER SEWER MAINS ARE TO
BE EITHER SN8 PLAIN SIDED OR SEWERPRO.
(MAXIMUM DEPTH ULTRARIB 3.0m)

SIGNED_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

LAND DEVELOPMENT CO-ORDINATOR
DEVELOPMENT SERVICES

## CONSTRUCTION NOTES

1. CONSTRUCTION OF SEWER AND WATER MAINS TO BE IN ACCORDANCE WITH BARWON WATER STANDARD SPECIFICATIONS "CONSTRUCTION OF GRAVITY SEWERS AND RISING MAINS" AND "CONSTRUCTION OF WATER MAINS".
2. EVERY ENDEAVOUR TO ENSURE THE LOCATION OF ALL EXISTING SERVICES ON THE PLAN ARE CORRECT HOWEVER ACTUAL LOCATIONS ARE TO BE CHECKED ON SITE PRIOR TO COMMENCEMENT OF EXCAVATION.
3. NOMINAL SIZE OF WATER MAINS INDICATED IN MILLIMETERS, OFFSETS ARE INDICATED IN METRES.
4. ALL SEWER PIPES ARE 150 Ø mm UNLESS OTHERWISE SHOWN.

### PIPE TYPES

| | |
|---|---|
| ASBESTOS CEMENT | AC |
| CAST IRON CEMENT LINED | CICL |
| DUCTILED CEMENT LINED | DICL |
| MILD STEEL CEMENT LINED | MSCL |
| POLYVINYL CHLORIDE | PVC |
| POLYETHELENE (AS SPECIFIED) | PE |
| REINFORCED CONCRETE | RC |
| VITREOUS CLAY | VC |

### FITTINGS AND SYMBOLS

WATER
CHANGE OF PIPE SIZE
MAINS NOT CONNECTED
MAINS IN CONDUIT
VALVE
NON RETURN VALVE
FIRE PLUG
DEAD END CAP

SEWER
TYPE "A" JUMP UP
TYPE "B" JUMP UP
TYPE "C" SLIDE LINE
OBLIQUE JUNCTION
TYPE "A" SPECIAL

### OTHER U/G SERVICES

EXISTING WATER MAIN
STORM WATER
GAS
TELSTRA
ELECTRICITY ● (POLE)
EXISTING SEWER

PETER BERRY & ASSOCIATES PTY LTD
153 YARRA STREET, GEELONG 3220 TEL 5223 2799 FAX 5223 2901

| AMENDMENTS | | |
|---|---|---|
| REV | DESCRIPTION | DATE |

EXTENSION No L014287

ANDERSON STREET SUBDIVISION - STAGE 3
WINCHELSEA
SHEET 3 OF 4

| DESIGNED JULY '17 | DRAWN JULY '15 | CHECKED |
|---|---|---|
| D.L. BERRY | D.L. BERRY | D.L. BERRY |
| MGR. PETER BERRY | EXECUTIVE MGR. | |

SCALES - PLAN - SECTIONS - HORIZ : 1:500 VERT : 1:100
REVISION : A
A1




| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Datum R.L. | 81.00 | | | | | | | | |
| APPROX DEPTH FINISHED SURFACE TO INVERT | 3.54 | 3.51 | | | 3.25 | 3.22 | | 2.63 | 2.60 |
| INVERT OF PIPE R.L. | 87.61 | 87.64 | | | 88.14 | 88.17 | | 89.16 | 89.19 |
| FINISHED SURFACE R.L. | 91.15 | | | | 91.39 | | | 91.79 | |
| EXISTING SURFACE R.L. | 91.15 | | | | 91.72 | | | 92.04 | |
| DISTANCE | 0.00 | | | | 60.00 | 0.00 | | 98.85 | |

HOUSE CONNECTION DETAILS:

| LINE NO. | MANHOLE NO. | HC NO. | LOT NAME | CONNECTION TYPE | CHAINAGE | IL SEWER | IL BRANCH | BRANCH HEIGHT |
|---|---|---|---|---|---|---|---|---|
| 1 | @ MH 3 | 1 | FUT | TM Special | 14.00 | 86.83 | 90.43 | 3.60 |
| 1 | @ MH 4 | 2 | FUT | B Special | 50.55 | 87.15 | 90.75 | 3.60 |
| 1 | MH 4 | 3 | FUT | B Special | 4.00 | 88.29 | 90.69 | 2.40 |
| 1 | MH 4 | 4 | FUT | TM Special | 5.00 | 88.30 | 90.70 | 2.40 |
| 1 | MH 4 | 5 | FUT | B Special | 23.00 | 88.45 | 90.65 | 2.20 |
| 1 | MH 4 | 6 | FUT | TM Special | 24.00 | 88.46 | 90.66 | 2.20 |
| 1 | MH 4 | 7 | FUT | B Special | 43.00 | 88.62 | 90.62 | 2.00 |
| 1 | MH 4 | 8 | FUT | TM Special | 44.00 | 88.63 | 90.63 | 2.00 |
| 1 | MH 5 | 9 | FUT | B | 1.00 | 88.82 | 90.72 | 1.90 |
| 1 | MH 5 | 10 | FUT | A Special | 2.00 | 88.83 | 90.73 | 1.90 |
| 1 | MH 5 | 11 | 49 | B | 21.00 | 89.07 | 90.77 | 1.70 |
| 1 | MH 5 | 12 | FUT | A Special | 22.00 | 89.08 | 90.78 | 1.70 |
| 1 | MH 5 | 13 | 48 | B | 41.00 | 89.32 | 90.92 | 1.60 |
| 1 | MH 5 | 14 | FUT | A Special | 42.00 | 89.33 | 90.93 | 1.60 |
| 1 | MH 6 | 15 | 46 | B | 2.00 | 89.61 | 90.91 | 1.30 |
| 1 | @ SMS 1 | 16 | 47 | A Special | 26.60 | 90.10 | 90.80 | 0.70 |

| LINE NO. | MANHOLE NO. | HC NO. | LOT NAME | CONNECTION TYPE | CHAINAGE | IL SEWER | IL BRANCH | BRANCH HEIGHT |
|---|---|---|---|---|---|---|---|---|
| 2 | Ex MH F | 17 | 40 | TM Special | 15.00 | 87.77 | 90.27 | 2.50 |
| 2 | Ex MH F | 18 | 41 | TM Special | 36.00 | 87.94 | 90.34 | 2.40 |
| 2 | Ex MH F | 19 | 42 | TM Special | 57.00 | 88.11 | 90.41 | 2.30 |
| 2 | MH 7 | 20 | 43 | TM Special | 18.00 | 88.35 | 90.45 | 2.10 |
| 2 | MH 7 | 21 | 44 | TM Special | 39.00 | 88.56 | 90.56 | 2.00 |
| 2 | MH 7 | 22 | 45 | A Special | 60.00 | 88.77 | 90.67 | 1.90 |
| 2 | MH 7 | 23 | FUT | A Special | 81.00 | 88.98 | 90.68 | 1.70 |

| LINE NO. | MANHOLE NO. | HC NO. | LOT NAME | CONNECTION TYPE | CHAINAGE | IL SEWER | IL BRANCH | BRANCH HEIGHT |
|---|---|---|---|---|---|---|---|---|
| 3 | Ex MH D | 24 | 51 | A Special | 4.00 | 89.21 | 90.21 | 1.00 |
| 3 | @ SMS 2 | 25 | 50 | B | 28.65 | 89.70 | 90.40 | 0.70 |




NOTE: (SEE NOTE 13 ON SHEET 1)
- PE SERVICE IS TO HAVE A COPPER TRACE WIRE
- SERVICE PIPE BETWEEN MAIN FERRULE AND BALL VALVE TO BE A CONTINUOUS LENGTH (ie NO JOINS)
- SERVICE TO BE TYPE 'B' COPPER OR CLASS 12 TYPE 50 PE.
- BALL VALVE TO BE PLUGGED WITH A PLASTIC CAP AND COVERED WITH A PLASTIC COVER.

DRY TAPPING INSTALLATION
(NOT TO SCALE)




DRY TAPPING PLAN
(NOT TO SCALE)

NOTE:

150mm DIAMETER SEWER MAINS ARE TO
BE EITHER SN8 PLAIN SIDED OR SEWERPRO.
(MAXIMUM DEPTH ULTRARIB 3.0m)

ACCEPTED BY BARWON WATER

WORKS SHALL NOT COMMENCE UNTIL PLANS SIGNED BY BARWON WATER

SIGNED _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

LAND DEVELOPMENT CO-ORDINATOR
DEVELOPMENT SERVICES

## CONSTRUCTION NOTES

1. CONSTRUCTION OF SEWER AND WATER MAINS TO BE IN ACCORDANCE WITH BARWON WATER STANDARD SPECIFICATIONS "CONSTRUCTION OF GRAVITY SEWERS AND RISING MAINS" AND "CONSTRUCTION OF WATER MAINS".
2. EVERY ENDEAVOUR TO ENSURE THE LOCATION OF ALL EXISTING SERVICES ON THE PLAN ARE CORRECT HOWEVER ACTUAL LOCATIONS ARE TO BE CHECKED ON SITE PRIOR TO COMMENCEMENT OF EXCAVATION.
3. NOMINAL SIZE OF WATER MAINS INDICATED IN MILLIMETERS, OFFSETS ARE INDICATED IN METRES.
4. ALL SEWER PIPES ARE 150 Ø mm UNLESS OTHERWISE SHOWN.

### PIPE TYPES

| | |
|---|---|
| ASBESTOS CEMENT | AC |
| CAST IRON CEMENT LINED | CICL |
| DUCTILED CEMENT LINED | DICL |
| MILD STEEL CEMENT LINED | MSCL |
| POLYVINYL CHLORIDE | PVC |
| POLYETHELENE (AS SPECIFIED) | PE |
| REINFORCED CONCRETE | RC |
| VITREOUS CLAY | VC |

### FITTINGS AND SYMBOLS

WATER
- CHANGE OF PIPE SIZE
- MAINS NOT CONNECTED
- MAINS IN CONDUIT
- VALVE
- NON RETURN VALVE
- FIRE PLUG
- DEAD END CAP

SEWER
- TYPE "A" JUMP UP
- TYPE "B" JUMP UP
- TYPE "C" SLIDE LINE
- OBLIQUE JUNCTION
- TYPE "A" SPECIAL

### OTHER U/G SERVICES

- EXISTING WATER MAIN
- STORM WATER
- GAS
- TELSTRA
- ELECTRICITY ●(POLE)
- EXISTING SEWER

PETER BERRY & ASSOCIATES PTY LTD
153 YARRA STREET, GEELONG 3220 TEL 5223 2799 FAX 5223 2901

| AMENDMENTS | | |
|---|---|---|
| REV | DESCRIPTION | DATE |

EXTENSION No L014287

ANDERSON STREET SUBDIVISION - STAGE 3
WINCHELSEA
SHEET 4 OF 4

| DESIGNED JULY '17 | DRAWN JULY '17 | CHECKED |
|---|---|---|
| D.L. BERRY | D.L. BERRY | D.L. BERRY |
| MGR. PETER BERRY | EXECUTIVE MGR. | |

SCALES - PLAN - SECTIONS - HORIZ : 1:500 VERT : 1:100
REVISION : A
A1